

IN THE CLAIMS:

1. (Currently Amended): A method for protecting a data transfer, comprising:
 - receiving a data transfer request, wherein the data transfer request comprises a request address;
 - determining whether the request address is within a generate address range;
 - sending generate information to a hardware computation engine in response to the request address being within the generate address range;
 - receiving a cyclical redundancy check value from the hardware computation engine; and
 - storing the cyclical redundancy check value.
2. (Original): The method of claim 1, wherein the generate address range is defined by generate base and limit registers.
3. (Original): The method of claim 1, wherein the hardware computation engine calculates the cyclical redundancy check value simultaneously with the data transfer.
4. (Original): The method of claim 1, wherein the generate address range maps to a protected data area in memory.
5. (Original): The method of claim 4, wherein the data transfer request is a write request.
6. (Original): The method of claim 5, further comprising writing data for the data transfer request into the protected data area.
7. (Original): The method of claim 1, further comprising:
 - determining whether the request address is within a check address range if the request address is not within a generate address range;

sending check information to the hardware computation engine;
receiving a cyclical redundancy check result from the hardware computation engine.

8. (Original): The method of claim 7, further comprising:

performing the data transfer without cyclical redundancy protection if the request address is not within the generate address range or the check address range.

9. (Original): The method of claim 7, wherein the generate address range and the check address range both map to a protected data area in memory.

10. (Original): The method of claim 1, wherein the generate information includes the request address and data to be transferred.

11. (Currently Amended): A method for protecting a data transfer, comprising:

receiving a data transfer request, wherein the data transfer request comprises a request address;

determining whether the request address is within a check address range;

sending check information to a hardware computation engine in response to the request address being within the check address range; and

receiving a cyclical redundancy check result from the hardware computation engine.

12. (Original): The method of claim 11, wherein the check address range is defined by check base and limit registers.

13. (Original): The method of claim 11, wherein the hardware computation engine checks the cyclical redundancy check value simultaneously with the data transfer.

14. (Original): The method of claim 11, wherein the cyclical redundancy check result includes error information.

15. (Original): The method of claim 14, further comprising storing the error information.

16. (Original): The method of claim 11, wherein the check address range maps to a protected data area in memory.

17. (Original): The method of claim 16, wherein the data transfer request is a write request.

18. (Original): The method of claim 17, further comprising writing data for the data transfer request into the protected data area.

19. (Original): The method of claim 16, wherein the data transfer request is a read request.

20. (Original): The method of claim 19, further comprising reading data for the data transfer request from the protected data area.

21. (Currently Amended): An apparatus for protecting a data transfer, comprising:
a memory interface logic;
a system memory coupled to the memory interface logic;
a hardware computation engine, wherein the hardware computation engine is coupled to the memory interface logic by a memory monitor bus and a memory read/write bus,

wherein the memory interface logic receives a data transfer request, wherein the data transfer request comprises a request address; determines whether the request address is within a generate address range; sends generate information to a hardware computation engine via the memory monitor bus in response to the request address being within the generate address range; receives a cyclical redundancy check value from the hardware computation engine via the memory read/write bus; and stores the cyclical redundancy check value in the system memory.

22. (Original): The apparatus of claim 21, wherein the generate address range is defined by generate base and limit registers.

23. (Original): The apparatus of claim 21, wherein the hardware computation engine calculates the cyclical redundancy check value simultaneously with the data transfer.

24. (Original): The apparatus of claim 21, wherein the generate address range maps to a protected data area in the system memory.

25. (Currently Amended): An apparatus for protecting a data transfer, comprising:

a memory interface logic;

a system memory coupled to the memory interface logic;

a hardware computation engine, wherein the hardware computation engine is coupled to the memory interface logic by a memory monitor bus and a memory read/write bus,

wherein the memory interface logic receives a data transfer request, wherein the data transfer request comprises a request address; ~~determining~~ determines whether the request address is within a check address range; sends check information to a hardware computation engine via the memory monitor bus in response to the request address being within the check address range; and receives a cyclical redundancy check result from the hardware computation engine via the memory read/write bus.

26. (Original): The apparatus of claim 25, wherein the check address range is defined by check base and limit registers.

27. (Original): The apparatus of claim 25, wherein the hardware computation engine checks the cyclical redundancy check value simultaneously with the data transfer.

28. (Original): The apparatus of claim 25, wherein the cyclical redundancy check result includes error information.

29. (Original): The apparatus of claim 28, wherein the memory interface logic stores the error information.

30. (Original): The apparatus of claim 25, wherein the check address range maps to a protected data area in the system memory.